


OFFERING SYSTEMS FOR:

- Transplanting
- Soil mixing and distribution
- Plug tray fillers
- Integrated seeding lines
- Dispensers and fillers for flats and pots
- Plug grading and consolidation
- Planting lines for cuttings
- Watering booms
- Stationary / movable conveyors
- Custom automation
- Labeling equipment
- Rolling bench growing systems
- Rolling bench automation
- Vision grading and shipping systems
- 24 hr. technical assistance
- Installation & service

300 Creekside Drive
Oberlin, Ohio 44074
Tel: 440-774-2981
1-800-354-3750
Fax: 440-775-2104
www.agrinomix.com



Specifications:

Speed:

- * 2 Row Tray: 1700* trays / hr
- * 3 Row Tray: 1100* trays / hr

*Based on 4" pots, larger pots will decrease #'s.

Power Requirement:

110 V, 4 A

Air Requirement:

5 CFM @ 80 PSI

Machine Dimensions:

84" long x 58" wide

Features:

- * Up 6" tall pots, 6 1/2" wide
- * Double head dispensing for speed
- * Dispenses square and round pots
- * Tray turning rail
- * Ready to integrate into transplanting line

Options:

The Versa² Pot Dispenser reduces labor requirements on high throughput production lines by automatically dispensing pots into shuttle trays using an advanced double head solution. This innovative dispenser design utilizes two vacuum cups per pot to securely grip pots on their inside side walls before inverting them to place them directly into the shuttle tray. This secure, high-speed transfer method is ideal for plastic pots that are not easily separated on gravity-feed style dispensing machines and for "press-fit" pot and shuttle tray designs. Issues that challenge a conventional dispenser like thin wall light-weight plastics, static electricity, wet pots, and close-fitting pots and shuttle trays present no problem for the Versa² Pot Dispenser.

